

Ultimate



Features

- 8MP (3840×2160) H.265+ full real-time encoding
- Voice annunciation and Two way Speech
- Al People & Vehicle Detection
- Red & Blue LED Warning Lights
- · Sensor Light or Colour at Night
- Facial Recognition
- 30~50m IR night view distance
- Meta Descriptive Tagging
- Triple Stream, 3D DNR, digital WDR
- PoE power or 12V DC
- 2.8 Fixed Lens
- IP67 ingress protection

Audible Perimeter Alert

When triggered, the camera can announce pre-recorded messages or siren
Automatically switches to 2-way audio mode.

Visual Perimeter Alert

Red and Blue Flashing LEDs to ward off intruders. Can be set to sensor light mode or white light mode to give colour at night.

Al People & Vehicle Detection

This advanced AI feature can detect people, vehicles allowing you to quickly search footage or be alerted via Push Notifications. Can be switched to facial recognition instead.



5 Cameras In One

Two Way Speech Audible Alerts Flashing Red and Blue Led Alerts Al Triggered White Sensor Light White Light for Colour at Night





Specifications

-	
Image Sensor	1 / 1.8" CMOS
Resolution	8MP (3840×2160), 2K, 3MP, 1080P, 720P, D1, CIF
Min. Illumination	0.008 lux @F1.6, AGC on; 0 lux with IR, White light
Lens	2.8mm Fixed lens @F1.6 AoV 109°
Day & Night	ICR Filter
Video Format	H.265+ / H.265 / H.264+ / H264 / MJPEG
Main Stream	60Hz: 8MP(1~30fps), 50Hz: 8MP(1~25fps)
Wide Dynamic	Digital WDR
Image Settings	ROI, Hue, Saturation, Brightness, Contrast, BLC, HWDR
	Sharpen, Noise Reduction, Distortion Correction
Audio	Internal Mic x1, External Mic input x1
	Internal Speaker, Audio output x1
Alarm interface	1x alarm input, 1x dry contact relay output
Intelligence Analytics	Tripwire, Intrusion, Face detection, Target Count, Exception
Smart Alarm	Intelligence Analytics (people & vehicle,face), Motion
Illumination	30~40m IR distance, 30~40m White distance
Smart IR	Switchable
SD Card Recording	Motion triggered recording. Up to 256GB capacity
Remote	Edge Browser, CMS Software up to 4 simultaneous users
Protocol	TCP/IP,UDP,DHCP,NTP,RTSP,PPPoE,DDNS,SMTP,FTP
Housing Rating	IP66
Power Supply	DC 12V / 48V PoE
Power Usage	<12.5W with IR on
Operating Env.	-30°~ 60°C, <95% Humidity (non-condensing)
Dimensions	Ø 130 x 110(H)
Weight	0.64kg



Product specifications and appearance subject to change without notice

Mounting Accessories

JB-303

Ledge 2

